



|                        |       |       |       |       |       |       |       |       |       |
|------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Rahmengrößennummer     | 44 cm | 47 cm | 50 cm | 52 cm | 54 cm | 56 cm | 58 cm | 60 cm | 62 cm |
| Laufgradgröße          | 700c  | 700c  | 700c  | 700c  | 700c  | 700c  | 700c  | 700c  | 700c  |
| A Sitzrohr             | 39.0  | 42.0  | 45.0  | 47.5  | 50.0  | 52.5  | 54.8  | 56.7  | 58.6  |
| B Sitzwinkel           | 74.6° | 74.6° | 74.6° | 74.2° | 73.7° | 73.3° | 73.0° | 72.8° | 72.5° |
| C Steuerrohrlänge      | 9.5   | 11.0  | 13.0  | 14.5  | 16.0  | 17.5  | 19.5  | 22.0  | 24.5  |
| D Lenkwinkel           | 70.3° | 71.0° | 71.1° | 71.3° | 71.3° | 71.9° | 72.0° | 72.1° | 72.1° |
| E Effektives Oberrohr  | 50.1  | 50.9  | 51.9  | 53.0  | 54.2  | 55.4  | 56.7  | 57.9  | 59.3  |
| G Tretlagerabsenkung   | 8.0   | 8.0   | 8.0   | 8.0   | 8.0   | 7.8   | 7.8   | 7.5   | 7.5   |
| H Kettenstrebenlänge   | 42.0  | 42.0  | 42.0  | 42.0  | 42.0  | 42.0  | 42.5  | 42.5  | 42.5  |
| I Offset               | 5.3   | 5.3   | 5.3   | 5.3   | 5.3   | 4.8   | 4.8   | 4.8   | 4.8   |
| J Trail                | 6.6   | 6.1   | 6.0   | 5.9   | 5.9   | 6.1   | 6.0   | 5.9   | 5.9   |
| K Radstand             | 98.3  | 98.6  | 99.6  | 100.3 | 101.0 | 100.8 | 102.2 | 103.2 | 104.2 |
| L Überstandshöhe       | 65.7  | 68.6  | 71.6  | 73.5  | 75.4  | 77.6  | 79.6  | 81.7  | 83.5  |
| M Rahmen-Reach         | 36.0  | 36.4  | 36.8  | 37.1  | 37.4  | 37.7  | 38.0  | 38.3  | 38.6  |
| N Rahmen-Stack         | 51.0  | 52.7  | 54.6  | 56.1  | 57.5  | 59.1  | 61.1  | 63.2  | 65.6  |
| Sattelstrebenhöhe min. | 53.5  | 55.5  | 58.5  | 61.5  | 64    | 67    | 69    | 71    | 73    |
| Sattelstrebenhöhe max. | 63    | 65    | 68    | 71    | 73.5  | 76.5  | 78.5  | 80.5  | 82.5  |